

PRODUCT NAME X-TEND FOUR WAY LUBE

SECTION 04: FIRE AND EXPLOSION DATA

FLAMMABILITY YES

IF YES, UNDER WHICH CONDITIONS? EXCESSIVE HEAT, SPARKS AND OPEN FLAME.

MEANS OF EXTINCTION DRY CHEMICAL, CO₂ FOAM.

SPECIAL PROCEDURES WATER FROM FOGGING NOZZLES MAY BE USED TO COOL CLOSED
CONTAINERS TO PREVENT PRESSURE BUILDUP IF EXPOSED TO
EXTREME HEAT. FULL PROTECTIVE EQUIPMENT INCLUDING SELF
CONTAINED BREATHING APPARATUS SHOULD BE WORN IN A FIRE
INVOLVING THIS MATERIAL.

FLASHPOINT (°C) AND METHOD 78 TAG CLOSED CUP

UPPER EXPLOSION LIMIT (% BY VOLUME) 9.5

LOWER EXPLOSION LIMIT (% BY VOLUME) 0.6

AUTOIGNITION TEMPERATURE (°C) 215

HAZARDOUS COMBUSTION PRODUCTS HYDROCARBON FUMES AND SMOKE. CARBON MONOXIDE WHERE
COMBUSTION IS INCOMPLETE.

EXPLOSION DATA

SENSITIVITY TO MECHANICAL IMPACT NA

SENSITIVITY TO STATIC DISCHARGE NA

SECTION 05: REACTIVITY DATA

CHEMICAL STABILITY YES

IF NO, UNDER WHICH CONDITIONS?

INCOMPATIBILITY TO OTHER SUBSTANCES YES

IF SO, WHICH ONES? STRONG OXIDIZING AGENTS.

REACTIVITY AND UNDER WHAT CONDITIONS? NA

HAZARDOUS DECOMPOSITION PRODUCTS HYDROCARBON FUMES AND SMOKE, CO IF COMBUSTION IS
INCOMPLETE.

SECTION 06: TOXICOLOGICAL PROPERTIES

ROUTE OF ENTRY:

SKIN CONTACT MAY CAUSE IRRITATION.

SKIN ABSORPTION NO DATA AVAILABLE.

EYE CONTACT MAY CAUSE IRRITATION.

INHALATION INHALATION OF SOLVENTS MAY CAUSE IRRITATION. PROPELLANT IS A SIMPLE ASPHYXIANT.

INGESTION MAY CAUSE HEADACHE, NAUSEA, VOMITING AND WEAKNESS.

PRODUCT NAME X-TEND FOUR WAY LUBE

EFFECTS OF ACUTE EXPOSURE : DIZZINESS, NAUSEA. IRRITATION TO SKIN AND EYES.
 EFFECTS OF CHRONIC EXPOSURE : SOLVENTS MAY CAUSE DEFATTING ,DERMATITIS.

EXPOSURE LIMITS SEE SECTION 2

IRRITANCY OF MATERIAL SLIGHT

SENSITIZATION OF MATERIAL UNKNOWN

SYNERGISTIC MATERIALS NONE KNOWN

CARCINOGENICITY, REPRODUCTIVE EFFECTS,
 TERATOGENICITY, MUTAGENICITY THE INGREDIENTS OF THIS PRODUCT ARE NOT LISTED AS
 CARCINOGENS BY NTP, (NATIONAL TOXICOLOGY
 PROGRAM), NOT REGULATED AS CARCINOGENIC BY
 OSHA, AND HAVE NOT BEEN EVALUATED BY IARC NOR BY ACGIH.

SECTION 07: PREVENTIVE MEASURES

PERSONAL PROTECTIVE EQUIPMENT

GLOVES (SPECIFY) WEAR CHEMICAL RESISTANT GLOVES.

EYE (SPECIFY) SAFETY GLASSES

RESPIRATORY (SPECIFY) IF USED INDOORS ON A CONTINUOUS BASIS, USE OF A CARTRIDGE
 TYPE RESPIRATOR (NIOSH/MSHATC 23C OR EQUIVALENT) IS
 RECOMMENDED.

OTHER (SPECIFY) NA

ENGINEERING CONTROLS LOCAL EXHAUST, MECHANICAL IF USED ON A CONTINUOUS BASIS.

LEAK AND SPILL PROCEDURE REMOVE ALL SOURCES OF IGNITION. USE INERT ABSORBENT
 MATERIAL AND NON-SPARKING TOOLS. AVOID BREATHING FUMES.
 VENTILATE AREA. PREVENT FROM ENTERING A WATERCOURSE.

WASTE DISPOSAL DO NOT PUNCTURE OR INCINERATE CONTAINERS, EVEN WHEN EMPTY.
 DISPOSE OF IN ACCORDANCE WITH LOCAL, PROVINCIAL, AND FEDERAL
 REGULATIONS.

STORAGE REQUIREMENTS STORE IN COOL, WELL VENTILATED AREA, NOT TO EXCEED 50°C.

SPECIAL SHIPPING INFORMATION NA

PRODUCT NAME X-TEND FOUR WAY LUBE

SECTION 08: FIRST AID MEASURES

INHALATION: REMOVE PERSON TO FRESH AIR.

EYES AND SKIN: FLUSH AREA WITH LARGE AMOUNTS OF WATER.

INGESTION: DO NOT INDUCE VOMITING. CALL A PHYSICIAN IMMEDIATELY.

ADDITIONAL INFORMATION

SECTION 09: PREPARATION DATE OF M.S.D.S

PREPARED BY TECHNICAL DEPARTMENT

TELEPHONE NUMBER (905) 670-3881

DATE..... 5/5/2010

ADDITIONAL NOTES OR REFERENCES: