

PRODUCT NAME X-TEND POWER STEERING FLUID AND CONDITIONER (RED)

SECTION 04: FIRE AND EXPLOSION DATA

FLAMMABILITY NO
 IF YES, UNDER WHICH CONDITIONS? NA

MEANS OF EXTINCTION DRY CHEMICALS, CARBON DIOXIDE, WATER FOG, FOAM.

SPECIAL PROCEDURES USE WATER TO COOL FIRE EXPOSED CONTAINERS. FIRE FIGHTERS
 WEAR A SELF-CONTAINED BREATHING APPARATUS WHEN
 HYDROCARBONS ARE INVOLVED.

FLASHPOINT (°C) AND METHOD 200°C CLEVELAND OPEN CUP ASTM D-92
 UPPER EXPLOSION LIMIT (% BY VOLUME) ND
 LOWER EXPLOSION LIMIT (% BY VOLUME) ND
 AUTOIGNITION TEMPERATURE (°C) ND
 HAZARDOUS COMBUSTION PRODUCTS OXIDES, CARBON, NITROGEN, SULFUR.

EXPLOSION DATA

SENSITIVITY TO MECHANICAL IMPACT NA
 SENSITIVITY TO STATIC DISCHARGE NA

SECTION 05: REACTIVITY DATA

CHEMICAL STABILITY YES
 IF NO, UNDER WHICH CONDITIONS? HEAT, OPEN FLAME.

INCOMPATIBILITY TO OTHER SUBSTANCES YES
 IF SO, WHICH ONES? WATER, OXIDIZING AGENTS.

REACTIVITY AND UNDER WHAT CONDITIONS? NA
 HAZARDOUS DECOMPOSITION PRODUCTS OXIDES OF CARBON, NITROGEN, PHOSPHORUS, SULFUR, ZINC.

SECTION 06: TOXICOLOGICAL PROPERTIES

ROUTE OF ENTRY:

SKIN CONTACT YES
 SKIN ABSORPTION
 EYE CONTACT YES
 INHALATION YES
 INHALATION CHRONIC
 INGESTION YES

PRODUCT NAME X-TEND POWER STEERING FLUID AND CONDITIONER (RED)

EFFECTS OF ACUTE EXPOSURE : INHALATION: VAPORS GENERATED AT HIGH TEMPERATURES WILL CAUSE IRRITATION.

SWALLOWING: MAY CAUSE VOMITING, MILD IRRITATION TO THE DIGESTIVE TRACT.

SKIN CONTACT: PROLONGED CONTACT MAY CAUSE REDNESS OF SKIN TO SOME INDIVIDUALS.

EYE CONTACT: MAY CAUSE IRRITATION, REDNESS, WATERY EYES, BLURRED VISION.

EFFECTS OF CHRONIC EXPOSURE : NONE CURRENTLY KNOWN.

EXPOSURE LIMITS NA

IRRITANCY OF MATERIAL SLIGHT IRRITANT TO THE EYES.

SENSITIZATION OF MATERIAL NA

SYNERGISTIC MATERIALS NA

CARCINOGENICITY, REPRODUCTIVE EFFECTS,
TERATOGENICITY, MUTAGENICITY NOT LISTED BY IARC, NTP, OSHA

SECTION 07: PREVENTIVE MEASURES

PERSONAL PROTECTIVE EQUIPMENT

GLOVES (SPECIFY) OIL RESISTANT

EYE (SPECIFY) SAFETY GLASSES

RESPIRATORY (SPECIFY) NORMAL USE, NONE REQUIRED.

OTHER (SPECIFY) EYE WASH STATION

ENGINEERING CONTROLS LOCAL EXHAUST TO CONTROL MIST IF GENERATED.

LEAK AND SPILL PROCEDURE CONTAIN SPILLED LIQUID WITH INERT ABSORBENT, SHOVEL INTO
..... WASTE CONTAINERS. KEEP LIQUID OUT OF SEWERS AND
..... WATERWAYS.

WASTE DISPOSAL IN COMPLIANCE WITH ALL APPLICABLE FEDERAL, PROVINCIAL AND
..... LOCAL REGULATIONS.

HANDLING PROCEDURES AND EQUIPMENT CAUTION: COMBUSTIBLE LIQUID. HANDLE WITH CARE. AVOID SKIN
..... AND EYE CONTACT. KEEP OUT OF REACH OF CHILDREN.

STORAGE REQUIREMENTS STORE IN COOL DRY PLACE.

SPECIAL SHIPPING INFORMATION PETROLEUM OIL MA 1270 ORM-D

PRODUCT NAME X-TEND POWER STEERING FLUID AND CONDITIONER (RED)

SECTION 08: FIRST AID MEASURES

SWALLOWING: DO NOT INDUCE VOMITING. GIVE 2 CUPS OF WATER. CALL A PHYSICIAN.

SKIN: WASH AFFECTED AREA WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING.

EYES: FLUSH WITH WATER FOR 15 MINUTES. IF IRRITATION PERSISTS, CALL A PHYSICIAN.

INHALATION: REMOVE PERSON TO FRESH AIR TO AVOID FURTHER INHALATION.

ADDITIONAL INFORMATION

SECTION 09: PREPARATION DATE OF M.S.D.S

PREPARED BY TECHNICAL DEPARTMENT

TELEPHONE NUMBER (905) 670-3881

DATE..... 1/13/2011

ADDITIONAL NOTES OR REFERENCES: