


Wynn's Canada Ltd. 7090 Edwards Blvd. Mississauga, Ontario Canada L5S 1Z1
 (905) 670-3881 Fax: (905) 670-3829

MATERIAL SAFETY DATA SHEET

SECTION 01 : MATERIAL NAME/IDENTIFIER

PRODUCT NAME WYNN'S POWER STEERING SEALANT AND CONDITIONING FLUID (PART #61902,4)
MANUFACTURER WYNN'S CANADA LTD.
 7090 EDWARDS BLVD.
 MISSISSAUGA, ONTARIO L5S 1Z1
 CHEMTREC 24 HOUR EMERGENCY TELEPHONE # (703) 527-3887 CALL COLLECT

CHEMICAL NAME NA
CHEMICAL FAMILY HYDROCARBON BLEND
CHEMICAL FORMULA NA
TRADE NAME AND SYNONYMS NA
MOLECULAR WEIGHT NA
MATERIAL USE POWER STEERING FLUID

SECTION 02: HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENTS	APPROXIMATE CONDENSATION %	C.A.S., N.A. OR U.N. NUMBERS	LD/50, ROUTE, SPECIES	LC/50, ROUTE, SPECIES
PETROLEUM OIL	71.0	64742-58-1	NA	NA
PETROLEUM OIL	20.0	64741-97-5	NA	NA

SECTION 03: PHYSICAL DATA

PHYSICAL STATE LIQUID
ODOUR THRESHOLD (P.P.M) NA
SPECIFIC GRAVITY 0.88
VAPOUR PRESSURE NA
VAPOUR DENSITY (AIR=1) NA
EVAPORATION RATE NA
BOILING POINT (°C) >260
FREEZING POINT (°C) -34
SOLUBILITY IN WATER (20°C) 0%
% VOLATILE (BY VOLUME) 0%
pH NA
COEFFICIENT OF WATER/OIL DISTRIBUTION NA

PRODUCT NAME WYNN'S POWER STEERING SEALANT AND CONDITIONING FLUID

SECTION 04: FIRE AND EXPLOSION DATA

FLAMMABILITY NO

IF YES, UNDER WHICH CONDITIONS? NA

MEANS OF EXTINCTION DRY CHEMICALS, CARBON DIOXIDE , WATER FOG, FOAM.

SPECIAL PROCEDURES USE WATER TO COOL FIRE EXPOSED CONTAINERS, FIRE FIGHTERS
 WEAR A SELF-CONTAINED BREATHING APPARATUS WHEN
 HYDROCARBONS ARE INVOLVED IN FIRE.

FLASHPOINT (°C) AND METHOD 188°C CLEVELAND OPEN CUP ASTM D-92.

UPPER EXPLOSION LIMIT (% BY VOLUME) ND

LOWER EXPLOSION LIMIT (% BY VOLUME)..... ND

AUTOIGNITION TEMPERATURE (°C)..... ND

HAZARDOUS COMBUSTION PRODUCTS OXIDES OF CARBON, NITROGEN, ZINC.

EXPLOSION DATA

SENSITIVITY TO MECHANICAL IMPACT NA

SENSITIVITY TO STATIC DISCHARGE NA

SECTION 05: REACTIVITY DATA

CHEMICAL STABILITY YES

IF NO, UNDER WHICH CONDITIONS? HEAT OPEN FLAME.

INCOMPATIBILITY TO OTHER SUBSTANCES YES

IF SO, WHICH ONES? WATER, OXIDIZING AGENTS.

REACTIVITY AND UNDER WHAT CONDITIONS?..... NA

HAZARDOUS DECOMPOSITION PRODUCTS OXIDES OF CARBON, NITROGEN, PHOSPHORUS, ZINC.

SECTION 06: TOXICOLOGICAL PROPERTIES

ROUTE OF ENTRY:

SKIN CONTACT..... YES

SKIN ABSORPTION.....

EYE CONTACT YES

INHALATION..... YES

INHALATION CHRONIC

INGESTION..... YES

PRODUCT NAME WYNN'S POWER STEERING SEALANT AND CONDITIONING FLUID

EFFECTS OF ACUTE EXPOSURE : INHALATION: VAPORS GENERATED AT HIGH TEMPERATURE WILL CAUSE IRRITATION.

SWALLOWING: MAY CAUSE VOMITING. MILD IRRITATION TO THE DIGESTIVE TRACT.

SKIN CONTACT: PROLONGED CONTACT MAY CAUSE REDNESS OF SKIN TO SOME INDIVIDUALS.

EYE CONTACT: MAY CAUSE IRRITATION, REDNESS, WATERY EYES, BLURRED VISION.

EFFECTS OF CHRONIC EXPOSURE : NONE CURRENTLY KNOWN.

EXPOSURE LIMITS5mg/m³ AS A MIST.

IRRITANCY OF MATERIALSLIGHT IRRITANT TO THE EYES.

SENSITIZATION OF MATERIAL.....NA

SYNERGISTIC MATERIALSNA

CARCINOGENICITY, REPRODUCTIVE EFFECTS,
TERATOGENICITY, MUTAGENICITYNOT LISTED BY IARC, NTP, OSHA.

SECTION 07: PREVENTIVE MEASURES

PERSONAL PROTECTIVE EQUIPMENT

GLOVES (SPECIFY) OIL RESISTANT.

EYE (SPECIFY) SAFETY GLASSES

RESPIRATORY (SPECIFY) NORMAL USE, NONE REQUIRED.

OTHER (SPECIFY) EYE WASH STATION.

ENGINEERING CONTROLS LOCAL EXHAUST TO CONTROL MIST IF GENERATED.

LEAK AND SPILL PROCEDURE CONTAIN LIQUID WITH INERT ABSORBENT. SHOVEL INTO WASTE
..... CONTAINERS. KEEP LIQUID OUT OF SEWERS AND WATERWAYS.

WASTE DISPOSAL..... IN COMPLIANCE WITH ALL APPLICABLE FEDERAL, PROVINCIAL AND
..... LOCAL REGULATIONS.

HANDLING PROCEDURES AND EQUIPMENT CAUTION: COMBUSTIBLE LIQUID. HANDLE WITH CARE. AVOID SKIN
..... AND EYE CONTACT. KEEP OUT OF REACH OF CHILDREN.

STORAGE REQUIREMENTS STORE IN COOL DRY PLACE.

SPECIAL SHIPPING INFORMATION PETROLEUM OIL NA 1270 ORM-D.

PRODUCT NAME WYNN'S POWER STEERING SEALANT AND CONDITIONING FLUID

SECTION 08: FIRST AID MEASURES

SWALLOWING: DO NOT INDUCE VOMITING. GIVE 2 CUPS OF WATER. CALL A PHYSICIAN IMMEDIATELY.

SKIN: WASH AFFECTED AREA WITH SOAP AND WATER.

EYES: FLUSH WITH WATER FOR 15 MINUTES. CALL A PHYSICIAN IF IRRITATION PERSISTS.

INHALATION: REMOVE PERSON TO FRESH AIR TO AVOID FURTHER INHALATION.

ADDITIONAL INFORMATION

SECTION 09: PREPARATION DATE OF M.S.D.S

PREPARED BY TECHNICAL DEPARTMENT

TELEPHONE NUMBER (905) 670-3881

DATE..... 1/13/2011

ADDITIONAL NOTES OR REFERENCES: