



**Wynn's Canada Ltd.** 7090 Edwards Blvd. Mississauga, Ontario Canada L5S 1Z1  
(905) 670-3881 Fax: (905) 670-3829

## MATERIAL SAFETY DATA SHEET

### SECTION 01 : MATERIAL NAME/IDENTIFIER

**PRODUCT NAME** ..... X-TEND HEAVY DUTY STOP SQUEAK (PART #63501)  
**MANUFACTURER** ..... WYNN'S CANADA LTD.  
 7090 EDWARDS BLVD.  
 MISSISSAUGA, ONTARIO L5S 1Z1  
 CHEMTREC 24 HOUR EMERGENCY TELEPHONE # (703) 527-3887 CALL COLLECT

CHEMICAL NAME..... NA  
 CHEMICAL FAMILY ..... NA  
 CHEMICAL FORMULA..... 63501  
 TRADE NAME AND SYNONYMS ..... NA  
 MOLECULAR WEIGHT ..... NA  
 MATERIAL USE ..... NA

### SECTION 02: HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENTS	APPROXIMATE CONDENSATION %	C.A.S., N.A. OR U.N. NUMBERS	LD/50, ROUTE, SPECIES	LC/50, ROUTE, SPECIES
ISOPROPYL ALCOHOL	90-97%	67-63-0	ND	ND
GRAPHITE	<5	7782-42-5	ND	ND

### SECTION 03: PHYSICAL DATA

PHYSICAL STATE ..... BLACK LIQUID  
 ODOUR THRESHOLD (P.P.M) ..... ND  
 SPECIFIC GRAVITY ..... 0.79  
 VAPOUR PRESSURE ..... 31.2  
 VAPOUR DENSITY (AIR=1)..... NA  
 EVAPORATION RATE ..... ND  
 BOILING POINT (°C)..... 83<sup>0</sup>C  
 FREEZING POINT (°C) ..... ND  
 SOLUBILITY IN WATER (20°C) ..... MISCIBLE  
 % VOLATILE (BY VOLUME) ..... 97  
 pH ..... ND  
 COEFFICIENT OF WATER/OIL DISTRIBUTION ..... ND

**PRODUCT NAME** ..... X-TEND HEAVY DUTY STOP SQUEAK

### SECTION 04: FIRE AND EXPLOSION DATA

FLAMMABILITY ..... YES

IF YES, UNDER WHICH CONDITIONS? ..... HEAT, SPARK, OR OPEN FLAME.

MEANS OF EXTINCTION ..... USE FOAM, CARBON DIOXIDE, DRY CHEMICAL.

SPECIAL PROCEDURES ..... FIRE FIGHTERS WEAR A SELF-CONTAINED BREATHING APPARATUS.

FLASHPOINT (°C) AND METHOD ..... 14°C

UPPER EXPLOSION LIMIT (% BY VOLUME) ..... ND

LOWER EXPLOSION LIMIT (% BY VOLUME) ..... ND

AUTOIGNITION TEMPERATURE (°C) ..... ND

HAZARDOUS COMBUSTION PRODUCTS ..... ND

#### EXPLOSION DATA

SENSITIVITY TO MECHANICAL IMPACT ..... ND

SENSITIVITY TO STATIC DISCHARGE ..... ND

### SECTION 05: REACTIVITY DATA

CHEMICAL STABILITY ..... STABLE

IF NO, UNDER WHICH CONDITIONS? .....

INCOMPATIBILITY TO OTHER SUBSTANCES ..... YES

IF SO, WHICH ONES? ..... STRONG OXIDIZERS

REACTIVITY AND UNDER WHAT CONDITIONS? ..... NA

HAZARDOUS DECOMPOSITION PRODUCTS ..... CARBON MONOXIDE AND CARBON DIOXIDE.

### SECTION 06: TOXICOLOGICAL PROPERTIES

ROUTE OF ENTRY:

SKIN CONTACT ..... YES

SKIN ABSORPTION ..... YES

EYE CONTACT ..... YES

INHALATION ..... YES

INHALATION CHRONIC ..... YES

INGESTION ..... YES

EFFECTS OF ACUTE EXPOSURE: INGESTION-MAY CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING AND DIARRHEA. SKIN CONTACT-MAY CAUSE IRRITATION AND DERMATITIS. EYE CONTACT-MAY CAUSE SEVERE IRRITATION, BURNING SENSATION, BLURRED VISION. INHALATION-MAY CAUSE NASAL AND RESPIRATORY IRRITATION, DIZZINESS, NAUSEA, HEADACHE.

EFFECTS OF CHRONIC EXPOSURE: THIS MATERIAL HAS NOT BEEN IDENTIFIED AS A CARCINOGEN BY NTP, IARC OR OSHA.

**PRODUCT NAME** ..... X-TEND HEAVY DUTY STOP SQUEAK

EXPOSURE LIMITS ..... ND

IRRITANCY OF MATERIAL ..... ND

SENSITIZATION OF MATERIAL ..... ND

SYNERGISTIC MATERIALS ..... ND

CARCINOGENICITY, REPRODUCTIVE EFFECTS,  
TERATOGENICITY, MUTAGENICITY ..... ND

**SECTION 07: PREVENTIVE MEASURES**

**PERSONAL PROTECTIVE EQUIPMENT**

GLOVES (SPECIFY) ..... SOLVENT RESISTANT GLOVES

EYE (SPECIFY) ..... SAFETY GOGGLES

RESPIRATORY (SPECIFY) ..... NORMAL USE

OTHER (SPECIFY) EYE WASH STATION IS RECOMMENDED. . EFFECTS OF CHRONIC EXPOSURE: THIS MATERIAL HAS NOT BEEN IDENTIFIED AS A CARCINOGEN BY NTP, IARC OR OSHA

ENGINEERING CONTROLS ..... ND

LEAK AND SPILL PROCEDURE ..... ELIMINATE ALL IGNITION SOURCES. PREVENT ENTRY. VENTILATE AREA.  
..... USE INERT ABSORBANT MATERIAL TO ABSORB SPILLED LIQUID.  
..... SHOVEL INTO CONTAINERS. PREVENT LIQUID FROM ENTERING INTO  
..... SEWERS AND WATERWAYS.

WASTE DISPOSAL ..... DISPOSE OF IN ACCORDANCE WITH FEDERAL, PROVINCIAL AND LOCAL  
..... REGULATIONS.

HANDLING PROCEDURES AND EQUIPMENT ..... USE ADEQUATE VENTILATION AND AVOID EYE CONTACT.

STORAGE REQUIREMENTS ..... STORE IN A COOL, DRY PLACE.

SPECIAL SHIPPING INFORMATION ..... ND

**PRODUCT NAME** ..... X-TEND HEAVY DUTY STOP SQUEAK

**SECTION 08: FIRST AID MEASURES**

INGESTION - KEEP INDIVIDUAL CALM AND SEEK MEDICAL ATTENTION IMMEDIATELY.

SKIN CONTACT - REMOVE CONTAMINATED CLOTHING. WASH AFFECTED AREA WITH SOAP AND WATER.

EYE CONTACT - FLUSH EYES WITH WATER FOR 15 MINUTES. IF IRRITATION PERSISTS, CALL FOR MEDICAL HELP.

INHALATION - REMOVE PERSON TO FRESH AIR TO AVOID FURTHER INHALATION.

ADDITIONAL INFORMATION

---

**SECTION 09: PREPARATION DATE OF M.S.D.S**

PREPARED BY ..... TECHNICAL DEPARTMENT

TELEPHONE NUMBER ..... (905) 670-3881

DATE..... 3/18/2011

**ADDITIONAL NOTES OR REFERENCES:**