



# MATERIAL SAFETY DATA SHEET

## Wynn's Universal Synthetic Power Steering Fluid

WYNN'S  
A division of Illinois Tool Works Inc.  
1151 West Fifth Street  
Azusa, California 91702

**EMERGENCY TELEPHONE NUMBER:**  
Chemtrec (800) 424-9300  
**INFORMATION TELEPHONE NUMBER:**  
Wynn's (626) 334-0231

### PRODUCT IDENTIFICATION

PRODUCT NAME	EFFECTIVE DATE	PRODUCT CODE
Wynn's Universal Synthetic Power Steering Fluid	03-17-2011	A4801
CHEMICAL NAME	CAS NUMBER	
N/A	N/A	

### HAZARDOUS INGREDIENTS

COMMON NAME	CHEMICAL NAME	CAS NO.	OSHA PEL	ACGIH TLV-TWA
Polyalphaolefin	Polyalphaolefin	68649-11-6	5 mg/m <sup>3</sup> as Mist	5 mg/m <sup>3</sup> as mist
Acrylic Copolymer	Acrylic Copolymer	68171-50-6	None Established	None Established

Contains no other ingredients now known to be hazardous as defined by OSHA 29CFR 1910.1000(z) and 29CFR 1910.1200.

### PHYSICAL DATA

These data are approximate or typical values and should not be used as precise specifications. Unless otherwise noted values are at 20°C(68°F) and 760 mmHg (1 atm).

<b>Boiling Point/Range</b>	>500°F (>260°C)	<b>Freeze Point</b>	N/D
<b>Specific Gravity (H<sub>2</sub>O=1) @ 15.6°C</b>	0.83	<b>Vapor Pressure (mm Hg)</b>	<0.1
<b>Vapor Density (Air =1)</b>	>1	<b>Solubility in Water (%)</b>	0%
<b>% Volatiles by Volume</b>	Negligible	<b>Evaporation Rate (Butyl Acetate = 1)</b>	<1
<b>pH (as is)</b>	N/A	<b>pH (dilute) @ %</b>	N/A
<b>Appearance</b>	Clear green liquid	<b>Odor</b>	Mild

N/D - Not Determined

N/A - Not Applicable

< = Less Than

> = Greater Than

---

## FIRE AND EXPLOSION HAZARD DATA

---

**Flash Point** >200°F(>93°C) **Method** Pensky - Martens Closed Cup ASTM D-93

**Flammable or Explosive Limits** (Approximate percent by volume in air)

Lower (LEL) N/D Upper (UEL) N/D

**Hazard Class Identification**

	<b>Flammability</b> 1		<b>Hazard Code</b> 0 - Least (insignificant)
<b>Health</b> 2		<b>Reactivity</b> 0	1 - Slight
	<b>Other</b> --		2 - Moderate
			3 - High
			4 - Extreme

**Extinguishing Media**

Dry chemicals, carbon dioxide, water spray, foam.

**Special Fire Fighting Procedures**

Use water only to cool fire exposed containers. Fire fighters wear a self contained breathing apparatus.

**Unusual Fire and Explosion Hazards**

Combustion will produce smoke and toxic fumes.

---

## REACTIVITY DATA

---

**Stability**

Stable.

**Conditions to Avoid**

Heat, open flame.

**Materials to Avoid**

Strong oxidizing agents.

**Hazardous Decomposition or Combustion Products**

Thermal decomposition may produce oxides of carbon, nitrogen, sulfur, silicone.

**Hazardous Polymerization** (conditions)

Will not occur.

---

## HEALTH HAZARDS/ROUTES OF ENTRY

---

### Signs, Symptoms and Effects of Overexposure

- Ingestion** (swallowing) May be harmful or fatal if swallowed. Due to its low viscosity, it may enter lungs during swallowing or vomiting. Once in lungs serious damage may occur.
- Skin Contact** Can be absorbed through skin on prolonged contact. Single contact, no effect likely. Prolonged and repeated contact can result in defatting and drying of the skin. Can cause redness and itching.
- Eye Contact** May cause irritation, burning, blurred vision and redness.
- Inhalation** (breathing) Inhalation can cause irritation to nose and throat and upper respiratory tract. Concentrated vapor respiration can cause dizziness, nausea and central nervous system damage.

### Other Effects of Prolonged/Repeated Overexposure

This material has not been identified as a carcinogen by NTP, IARC or OSHA. Kidney damage may occur if large quantities are swallowed.

---

## EMERGENCY AND FIRST AID PROCEDURES

---

- Ingestion** (swallowing) DO NOT induce vomiting. Call for medical help.
- Skin Contact** Remove contaminated clothing. Wash affected area with soap and water. Call for medical help.
- Eye Contact** Flush eyes with water for 15 minutes. If irritation persists call for medical help.
- Inhalation** (breathing) Remove person to fresh air to avoid further inhalation. Call for medical help.
- Comments** NOTE TO PHYSICIANS: If more than 2 ml per kg body weight has been ingested and vomiting has not occurred, emesis should be induced with medical supervision.

---

## SPILL OR RELEASE CONTROL PROCEDURES

---

### Steps to be taken in case material is released or spilled

Use absorbent sand, clay or vermiculite. Shovel into containers. Prevent liquid from entering into sewers and waterways.

### Waste Disposal Method

Dispose of in accordance with Federal, State and Local regulations.

**Environmental Hazard** (EPA-CWA, Section 311)

Spills of this material leading to surface waters where it will cause a sheen must be reported to the National Response Center (800) 424-8802.

**EPA Toxic Chemical Release Reporting**, 40CFR372(SARA313)

Chemical	CAS NO.	% in Product
N/Z	N/A	N/A

---

## HANDLING AND STORAGE

---

**Handling and Storage Precautions**

WARNING: Contains petroleum distillates. Avoid skin and eye contact. Avoid breathing of vapors. Keep away from heat and sparks. Use entire contents. DO NOT store opened containers.

**Other Precautions**

KEEP AWAY FROM CHILDREN.

---

## PERSONAL PROTECTION - EXPOSURE CONTROL

---

**Ventilation**

Provide adequate general or local ventilation to maintain concentrations below TLV/PEL limits.

**Respiratory Protection**

None normally required. If vapors exceed TLV/PEL values, use a NIOSH approved respirator

**Eye Protection**

Safety glasses with side-shields.

**Protective Gloves**

Chemical-resistant gloves.

**Other Protective Clothing or Equipment**

Eye wash station is recommended.

**Work/Hygienic Practices**

Personal cleanliness is always appropriate. Frequent washing minimizes chances of inadvertent exposure.

---

## TRANSPORTATION INFORMATION

---

### Department of Transportation (DOT) Classification

	Flammable Liquid		Corrosive
	Flammable Solid		Non-Flammable Gas
	Flammable Gas	X	Not Hazardous by DOT
	Combustible Liquid		Other:

### DOT Proper Shipping Name

N/A

### DOT ID Number

N/A

---

## DOCUMENTATION

---

Product Code No.: A48  
Previous Code No.: New

Issue Date: 03-17-2011  
Prior Date: 03-06-07

This information is, to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use.